

Serial No.: 09/812,472

Please replace the paragraph on page 7, lines 24-30 with the following paragraph:

A2 -- Optionally a toy set according to the invention may include a lighting source e.g., lamp 780, although the invention is not limited in that regard. The lamp 780 may be provided in an appropriate stand, commensurate with the dimensions of the toy figurine 718. The lamp 780 may be turned on and off, in agreement with a theme of the display. For example, a toy lamp 780 may receive inputs from the sensor 660 (shown in Fig. 6), to come on when certain environmental conditions are met, for example, when it is dark. In Fig. 7, the lamp 780 receives input from controller 770. --

Please replace the paragraph on page 8, lines 7-12 with the following paragraph:

A3 -- In addition, a toy set according to the invention may optionally include a detector e.g., sensor 660. The detector may be used to sense certain environmental conditions, for example, sensor 660 may be used to detect whether it is cold. The image data may be responsive to the detector, for example, if the sensor 660 senses that it is cold outside then the image data may be that of a fire in a fireplace as shown in Fig. 6. --

#### IN THE CLAIMS:

Please amend the claims as follows:

- A4 -- 1. (Amended) A toy set comprising:
- at least one panel having a first surface, the first surface adapted to simulate a wall to use with a toy figurine; and
  - a first display that is to be attached to the first surface, the first display adapted to receive a first set of image data, and to display a first image responsive to the first set of image data,
- wherein the image data is distinct from the wall simulated on the first surface of the panel.

Serial No.: 09/812,472

2. (Amended) The toy set of claim 1, wherein  
the panel has a data connection, and  
the display receives the first set of image data through the data connection.

3. (Amended) The toy set of claim 1, wherein  
at least one Velcro™-type strip is adapted to attach the first display to the  
panel.

174  
4. (Amended) The toy set of claim 1, wherein  
the display and the panel have at least one protrusion and mating opening,  
and  
attachment is by placing the protrusion in the mating opening. --

175  
-- 11. (Amended) The toy set of claim 10, wherein  
the receiving antenna is within the panel. --

-- 25. (Amended) An article comprising: a storage medium, said storage medium  
having stored thereon instructions, that, when executed by at least one device, result in:

waiting to receive a signal output from a detector indicative of a toy  
figurine characteristic; and

176  
if the signal is received, transmitting a first set of image data to a display  
associated with a panel to cause the display to display an image corresponding to the first  
set of image data,

wherein the panel is adapted to provide a first surface which simulates a  
wall to use with the toy figurine and the image data is distinct from the wall simulated on  
the first surface of the panel. --

Serial No.: 09/812,472

- 
- 29. (Amended) A method comprising:
- providing a panel having a first surface which simulates a wall to use with a toy figurine;
  - waiting to receive an output of a detector about a location of the toy figurine; and
  - if the output is received, transmitting a first set of image data to a display associated with the panel to cause the display to display an image corresponding to the first set of image data, wherein the image data is distinct from the wall simulated on the first surface of the panel.
- 
-